



LOGISTIC

STABUFILM 35 OR 70 ANTI-SLIP

HIGH DENSITY POLYETHYLENE FILM (HDPE)



COMPOSITION

- ▶ Anti-slip coating (top side)
- ▶ High density polyethylene film
- ▶ Anti-slip coating (bottom side)

QUALITY OF PRODUCT

- ▶ High non-slip properties - waterproof
- ▶ Flexible – transparent
- ▶ **100% recyclable**
- ▶ Tertiary packaging, indirect food contact

APPLICATION USE

- ▶ **Stabilize any packaging format**
- ▶ Recommendation : use for drums, pails, bags...
- ▶ Water barrier for surface, layers and as topcover
- ▶ Can be use direct on pallet, as layers and top cover
- ▶ Successful for all product goods

PALLETIZATION

- ▶ Width of rolls : 1200 mm
- ▶ Length of rolls : 500 meters for 35 µm
- ▶ Length of rolls : 300 meters for 70 µm
- ▶ Perforated at 800 mm or 1000 mm

SPECIFICATION SHEET

Paper type	High density polyethylene film		Standards
Weight	35 or 70 g/sqm		ISO 536
	Non-slip on Non-slip	Non-slip on paper	
Slide angle	≥ 75°	≥ 65°	NF Q 03-083
Static coefficient of friction	≥ 3,7	≥ 2	NF Q 03-082
Dynamic coefficient of friction	≥ 1	≥ 0,6	NF Q 03-082



TECHNICOAT
Solution

solution@cgp-coating.com - www.cgp-coating.com

